

68379

F.A.S. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
380	*	KNOX	35	3
* D4 CULVERT EXT/REPAIR 2006				

GENERAL NOTES

BITUMINOUS CONCRETE MIXTURE REQUIREMENTS

THE FOLLOWING MIXTURE REQUIREMENTS ARE APPLICABLE TO THIS PROJECT:

MIXTURE USES	CLASS D PATCH (BOTTOM LIFTS)	CLASS D PATCH (SURFACE LIFT)
AC/PG:	PG 64-22	PG 64-22
RAP% (MAX):	25%	15%
DESIGN AIR VOIDS:	4.2% @ N=50	4.2% @ N=50
MIXTURE COMPOSITION: (GRADATION MIXTURE)	IL 19.0	IL 9.5 OR 12.5
FRICITION AGGREGATE:	N. A.	MIX D

STATUS OF UTILITIES TO BE ADJUSTED

Mid-Century Telephone

ROUTE	OFFSET	LOCATION	TYPE OF UTILITY	TYPE OF CONFLICT	DISPOSITION
LOCATION 1	45' RT TO 42' LT	1935+10 TO 1936+25	12 PAIR COPPER CABLE	BOX CULVERT/RIPRAP	RELOCATE
LOCATION 3	38' RT TO 38' RT	1867+30 TO 1867+60	FIBER OPTIC	DITCH	RELOCATE
LOCATION 4	39' RT TO 39' RT	1850+00 TO 1850+50	FIBER OPTIC	BOX CULVERT	CAUTION

Geneseo Telephone Co.

ROUTE	OFFSET	LOCATION	TYPE OF UTILITY	TYPE OF CONFLICT	DISPOSITION
LOCATION 3	20' RT TO 20' RT	1867+30 TO 1867+60	BURIED TELEPHONE	BOX CULVERT	CAUTION
LOCATION 4	30' RT TO 30' RT	1850+00 TO 1850+50	BURIED TELEPHONE	BOX CULVERT	RELOCATE

AmerenCILCO

ROUTE	OFFSET	LOCATION	TYPE OF UTILITY	TYPE OF CONFLICT	DISPOSITION
LOCATION 3	30' RT TO 30' RT	1867+00 TO 1868+00	AERIAL ELECTRIC	EARTH EXCAVATION	CAUTION

REVISIONS	
NAME	DATE

ILLINOIS DEPARTMENT OF TRANSPORTATION
 GENERAL NOTES AND
 STATUS OF UTILITIES
 TO BE ADJUSTED